



DECLARATION OF PERFORMANCE

in accordance with Regulation (EU) no 305/2011
of the European Parliament and of the Council of 9 March 2011 laying down harmonized conditions for the marketing of
construction products and repealing Council Directive 89/106/EEC

SYSTEM OF ASSESSMENT AND VERIFICATION OF CONSTANCY OF PERFORMANCE carried out with the System 3

Product name	ENGINEERED OAK FLOOR
Name and address of the manufacturer	LACCY - KOŁCZYGŁOWY Spółka z o.o. Słupska 60, 77-140 Kołczygłowy
Name and address of the production plant	Plant in Barnowo
Harmonized standard	EN 14342:2005+A1:2008
Declared use of the product	Installation of wood flooring glued to concrete base for internal spaces of residential and public buildings
Product description	Multi-layer elements made of natural oak wood and birch plywood, identified according to the standard EN 13489, with total thickness 15 and 20 mm. The lot number marked on the back of each board.

DECLARED PERFORMANCE

No	Essential characteristics	Performance	Test results		Harmonized technical specification
1.	Reaction to fire	Reaction to fire class	class C _{fl} -s1		EN 13501-1:2007+A1:2009
2.1.	Release of hazardous substances	Formaldehyde emission	class E1		EN 717-1:2004
2.2.		Content of pentachlorophenol	<0.1ppm		CEN/TR 14823:2003
3.1.	Slip resistance	Pendulum Test Value (PTV)	Lacquered	81	CEN/TS 15676:2007
3.2.			Oiled	96	
3.3.			Unfinished/sanded	76	
4.1.	Thermal conductivity	Thermal resistance R	15 mm	0.08 m ² K/W	EN 14342:2005+A1:2008 p. 5.6.
4.2.			20 mm	0.11 m ² K/W	
5.	Durability	Biological durability class	Class 1		EN 14342:2005+A1:2008

Kołczygłowy, 27.09.2013

Signed for and on behalf of the manufacturer by:

Laccy - Kołczygłowy Sp. z o.o.
ul. Słupska 60; 77-140 Kołczygłowy
Tel.: +48 59 821 39 50
Fax: +48 59 821 39 59
e-mail: laccy@laccy.pl; www.laccy.pl

WICEPREZES ZARZĄDU
LACCY-KOŁCZYGŁOWY Sp. z o.o.
mgr Jacek Grzanka